Intertiki Client tab

Overview

Set up Intertiki Client (Slave) Sites using this tab

Related Topics
• reference

To Access

From the Intertiki page, click the Intertiki client tab.

Note

set up the Intertiki Master using the associated Intertiki server tab

Option	Description	Default
Intertiki	Allows several Tiki sites (slaves) to get authentication from a master Tiki site	Disabled
Client key for this site	This must match the shared key entered in the Master's key field.	None
Intertiki shared cookie	Causes a user who logs into or out of either the slave or master site to be automatically logged into or out of all other sites. The remember me login feature must be on.	Disabled
Master Tiki server	Master Tiki server that this client will obtain user authorizations from. △ Overrides manually registered local users □ None tw.o	None
Import user preferences	Client Tiki will copy the user preferences from the master server. A This will overwrite local user preferences every time the user logs in.	Disabled
Import user groups	Groups the user belongs to on the master server will be imported (along with their security definitions). A This will overwrite local groups every time a user logs in.	Disabled
Limit group import	This list will limit the group import feature to only those groups listed here. Comma-separated list of case-sensitive imported groups. Leave empty to avoid limitation.	None

Option	Description	Default
Intertiki	Allows several Tiki sites (slaves) to get authentication from a master Tiki site	Disabled
Client key for this site	This must match the shared key entered in the Master's key field.	None
Intertiki shared cookie	Causes a user who logs into or out of either the slave or master site to be automatically logged into or out of all other sites. The remember me login feature must be on.	Disabled
Master Tiki server	Master Tiki server that this client will obtain user authorizations from. △ Overrides manually registered local users □ None tw.o	None
Import user preferences	Client Tiki will copy the user preferences from the master server. A This will overwrite local user preferences every time the user logs in.	Disabled
Import user groups	Groups the user belongs to on the master server will be imported (along with their security definitions). A This will overwrite local groups every time a user logs in.	Disabled
Limit group import	This list will limit the group import feature to only those groups listed here. • Comma-separated list of case-sensitive imported groups. Leave empty to avoid limitation.	None

Option	Description	Default
Intertiki	Allows several Tiki sites (slaves) to get authentication from a master Tiki site	Disabled
Client key for this site	This must match the shared key entered in the Master's key field.	None
Intertiki shared cookie	Causes a user who logs into or out of either the slave or master site to be automatically logged into or out of all other sites. The remember me login feature must be on.	Disabled
Master Tiki server	Master Tiki server that this client will obtain user authorizations from. △ Overrides manually registered local users □ None tw.o	None

Option	Description	Default
Import user preferences	Client Tiki will copy the user preferences from the master server. A This will overwrite local user preferences every time the user logs in.	Disabled
Import user groups	Groups the user belongs to on the master server will be imported (along with their security definitions). A This will overwrite local groups every time a user logs in.	Disabled
Limit group import	This list will limit the group import feature to only those groups listed here. Comma-separated list of case-sensitive imported groups. Leave empty to avoid limitation.	None

Option	Description	Default
Intertiki	Allows several Tiki sites (slaves) to get authentication from a master Tiki site	Disabled
Client key for this site	This must match the shared key entered in the Master's key field.	None
Intertiki shared cookie	Causes a user who logs into or out of either the slave or master site to be automatically logged into or out of all other sites. The remember me login feature must be on.	Disabled
Master Tiki server	Master Tiki server that this client will obtain user authorizations from. △ Overrides manually registered local users □ None	None
Import user preferences	Client Tiki will copy the user preferences from the master server. A This will overwrite local user preferences every time the user logs in.	Disabled
Import user groups	Groups the user belongs to on the master server will be imported (along with their security definitions). A This will overwrite local groups every time a user logs in.	Disabled
Limit group import	This list will limit the group import feature to only those groups listed here. Comma-separated list of case-sensitive imported groups. Leave empty to avoid limitation.	None

Option	Description	Default
Intertiki	Allows several Tiki sites (slaves) to get authentication from a master Tiki site	Disabled
Client key for this site	This must match the shared key entered in the Master's key field.	None
Intertiki shared cookie	Causes a user who logs into or out of either the slave or master site to be automatically logged into or out of all other sites. The remember me login feature must be on.	Disabled
Master Tiki server	Master Tiki server that this client will obtain user authorizations from. △ Overrides manually registered local users □ None	None
Import user preferences	Client Tiki will copy the user preferences from the master server. A This will overwrite local user preferences every time the user logs in.	Disabled
Import user groups	Groups the user belongs to on the master server will be imported (along with their security definitions). A This will overwrite local groups every time a user logs in.	Disabled
Limit group import	This list will limit the group import feature to only those groups listed here. Comma-separated list of case-sensitive imported groups. Leave empty to avoid limitation.	None

Setting	Description
Add new server	
Name:	Set the name (label) to use for your target server as defined in the server name field of the master.
host:	The full URL of the master servers primary Tiki (ex: http://www.tiki.org)
port:	The port number the master tikiwiki responds to HTTP on (usually 80)
Path:	the full path (from the URL root) to the PHP file containing the XMLRPC handler on the server

Setting	Description
Groups:	Groups on the master to authenticate to (only auth users in the groups defined, case-sensitive)