

## Plugin Attributes

Use this [wiki plugin](#), introduced in [Tiki6](#), to assign generic attributes to the current object. Attributes are provided as parameters. For tiki.geo.lat,

```
{attributes tiki_geo_lat=...}
```

Removing the plugin or values in it will not remove the attributes. See [Object Attributes and Relations](#) for the available attributes.

## Usage

The plugin Attributes is not enabled by default, you can enable it from the Control Panel, Editing and Plugins, Plugins.

```
{attributes tiki_geo_lat="" tiki_geo_lon="" tiki_geo_google_zoom="" tiki_relation_target="" tiki_relation_source=""}
```

## Parameters

Assign generic attributes to the current object

*Introduced in Tiki 6.*


[Go to the source code](#)

*Preferences required:* wikiplugin\_attributes

### Parameters

*no parameters*

## Examples of using it to set fixed values and use them in a tracker

*This method was used in a Tiki12 shop and I retrieved the code *

In this use case we want to have fixed/editable values that can be used in different features of Tiki.

There is several advantages;

- Changing one value will impact many other objects (items, calculation, etc).
- Editing can be very limited (permissions to edit this page only)
- Editing can be super relaxed (permissions to edit this page only)
- It may help to keep fixed values through time (VAT may change from time to time however you need to keep the value for a specific date)

Here some example of plugin attributes in a wiki page and the usage in another place (mainly tracker field)

## Display a value using attribute in many wiki pages (plugin List)

**On the wiki page name PluginAttributes**

```
{attributes nice_guy_name="Bernard"}
```

**On any other wiki page**

```
{LIST()} {OUTPUT(report="y")} {CALC()}(attribute (object (str wiki page) (str PluginAttributes)) (property nice.guy.name)){CALC} is the first name of a nice guy name. {OUTPUT} {LIST}
```

Will produce:

*Bernard is the first name of a nice guy name.*

Note: This should work in many other places like Blogs, Articles, Forums, Modules, etc. where there is a wiki area and it accept the wiki syntax.

## Using a constant from the pluginAttributes in a tracker field calculation

**On the wiki page**

```
{attributes shop_general_handling_fees="0.2"}
```

**Calculation in a mathematical field type in a tracker**

```
(mul Price (attribute (object (str wiki page) (str Constants)) (property shop.general.handling.fees)))
```

## Using a constant from the pluginAttributes to return different value in a php file

On the wiki page

```
{attributes shop_XXA_minimum="499" shop_XXB_minimum="599"}
```

usage and condition in a php file

```
// check min amount $shop_constants = TikiLib::lib('attribute')->get_attributes('wiki page', 'Constants'); if  
($input->supplierOrderName->int() == TikiLib::symbols()->Supplier['XXA']) { $minimum =  
$shop_constants['shop.XXA.minimum']; } else if ($input->supplierOrderName->int() ==  
TikiLib::symbols()->Supplier['XXB']) { $minimum = $shop_constants['shop.XXB.minimum']; } else { throw new  
Denied(tr('Unsupported Shop')); }
```

## Using a constant from the pluginAttributes in a Smarty template

On the wiki page

```
{attributes shop_freeshipping_limit="699"}
```

```
{tr}Shipping{/tr} {if ($cart_total > $shop_constants.shop_freeshipping_limit)}0.00{else}{$flat_cost|escape}{/if} {*  
$prefs.payment_currency|escape *}
```

## Related pages

- [Object Attributes and Relations](#)
- [Mathematical Calculation Tracker Field](#)
- [PluginRelations](#)
- [PluginAddRelation](#)
- For all plugins\* [Wiki Plugin](#) - has links to all plugins and describes how the syntax works for a plugin
- [Mods Type Wikiplugins](#)

## Aliases

- [PluginAttribute](#)