

# Plugin HTML

This [wiki plugin](#) allows you to add any HTML (including scripts and objects) to a wiki page. This plugin was introduced in [Tiki3](#).

See also [PluginJS](#) and [PluginJQ](#).

×

## Note

Because users could potentially add unsafe scripts to a page, this plugin [must be validated](#) by a trusted contributor before becoming "live" on the page.

# Parameters

*Introduced in Tiki 3.*

[Go to the source code](#)

*Preferences required: wikipugin\_html*

Parameters	Accepted Values
(body of plugin)	
<b>tohead</b>	(blank) 0 1

---

## **Description**

---

HTML code

---

Insert the code in the HTML head section rather than in the body.

---

<b>Default</b>	<b>Since</b>
0	17.0

wiki

(blank)

0

1

Parse wiki syntax within the HTML code.

---

0

3.0

# Examples



# Basic syntax

```
{HTML()}
```

You can use **HTML here** including JavaScript, etc.

This is unsafe and thus, must be validated by a trusted editor

```
{HTML}
```

# Example 1

You could paste the code you get for a [Google Gadget](#), a [PayPal button](#), etc.

For example, using this code:

**Adding an HTML Iframe into a wiki page.**

```
{HTML()}  
  TikiFest Montreal Mars 2009 fr. from Régis Barondeau  
{HTML}
```

Will produce this presentation embedded in the page:

**[TikiFest Montreal Mars 2009 fr.](#) from [Régis Barondeau](#)**

# Example 2

Embedding some html object from a site serving embeddable videos (youtube, vimeo, etc):

```
{CENTER()}{HTML()}{HTML}{CENTER}
```

However the plugin call was not validated by the admins but denied, and this is what it would produce:

ⓘ PLUGIN EXECUTION WAS DENIED

# Example 3

Making a wiki link to look like a button of the same theme style that you are using. For instance, this code:

```
^{HTML()}Save changes with my custom button to the page PluginHTML, while you send also itemId in the url for PluginTrackerList magic,  
for instance (not used in this simple example){HTML}^
```

Would produce:

[Save changes](#)

# Example 4

When the parameter *wiki=1* is used, wiki syntax will be parsed in the content inside HTML plugin.

```
{HTML(wiki=1)}  
  This wiki syntax will be parsed to produce special characters:  
  * ''Some examples:'' ~amp~ ~lt~ ~c~  
  * __More examples:__ ~gt~ ~ldq~  
  * ~rdq~ ~lsq~  
  * ~rsq~  
  * ~~~~ --  
{HTML}
```

produces:

- This wiki syntax will be parsed to produce special characters:
- *Some examples:* ~amp~ ~lt~ ~c~
  - **More examples:** ~gt~ ~ldq~
  - ~rdq~ ~lsq~
  - ~rsq~
  - ~~~~

# Alternatives

There are others ways to include HTML in a page:

- Use the [WYSIWYG](#) editor. Note that Tiki will automatically filter potentially unsafe content.
- Enable the **Allow HTML in Wiki Pages** option. Note that Tiki will automatically filter potentially unsafe content.
- Use [PluginJS](#) to include JavaScript in a wiki page.

# Related pages

- [PluginTrackerList](#)