

Plugin HTML

This [wiki plugin](#) allows you to add any HTML (including scripts and objects) to a wiki page. This plugin was introduced in [Tiki3](#).

See also [PluginJS](#) and [PluginJQ](#).

Parameters

Introduced in Tiki 3.

[Go to the source code](#)

Preferences required: `wikiplugin_html`

Parameters	Accepted Values	Description	Default	Since
(body of plugin)		HTML code		
<code>tohead</code>	(blank) 0 1	Insert the code in the HTML head section rather than in the body.	0	17.0
<code>wiki</code>	(blank) 0 1	Parse wiki syntax within the HTML code.	0	3.0

Examples

Basic syntax

```
{HTML() }
```

You can use HTML here including JavaScript, etc.

This is unsafe and thus, must be validated by a trusted editor

```
{HTML}
```

Example 1

You could paste the code you get for a [Google Gadget](#), a [PayPal button](#), etc.

For example, using this code:

Adding an HTML Iframe into a wiki page.

```
{HTML() }
```

```
  TikiFest Montreal Mars 2009 fr. from Régis Barondeau
```

```
{HTML}
```

Will produce this presentation embedded in the page:

[TikiFest Montreal Mars 2009 fr.](#) from [Régis Barondeau](#)

Example 2

Embedding some html object from a site serving embeddable videos (youtube, vimeo, etc):

```
{CENTER()}{HTML()}{HTML}{CENTER}
```

However the plugin call was not validated by the admins but denied, and this is what it would produce:

 Plugin execution was denied

After argument validation by an editor, the execution of this plugin was denied. This plugin will eventually be removed or corrected.

Example 3

Making a wiki link to look like a button of the same theme style that you are using. For instance, this code:

```
^{HTML()}Save changes with my custom button to the page PluginHTML, while you send also itemId in the url for PluginTrackerList magic, for instance (not used in this simple example){HTML}^
```

Would produce:

Save changes with my custom button to the page PluginHTML, while you send also itemId in the url for PluginTrackerList magic, for instance (not used in this simple example)

Example 4

When the parameter *wiki=1* is used, wiki syntax will be parsed in the content inside HTML plugin.

```
{HTML(wiki=1)}
```

This wiki syntax will be parsed to produce special characters:

- * 'Some examples:'' ~amp~ ~lt~ ~c~
- * **More examples:**__ ~gt~ ~ldq~
- * ~rdq~ ~lsq~
- * ~rsq~
- * ~~~~ --

```
{HTML}
```

produces:

This wiki syntax will be parsed to produce special characters:

- *Some examples:* ~amp~ ~lt~ ~c~
- **More examples:** ~gt~ ~ldq~
- ~rdq~ ~lsq~
- ~rsq~
- ~~~

Alternatives

There are others ways to include HTML in a page:

- Use the [WYSIWYG](#) editor. Note that Tiki will automatically filter potentially unsafe content.
- Enable the **Allow HTML in Wiki Pages** option. Note that Tiki will automatically filter potentially unsafe content.
- Use [PluginJS](#) to include JavaScript in a wiki page.

Related pages

- [PluginTrackerList](#)