# **Plugin Tour**

#### Introduced in Tiki15

Use this wiki plugin to build your product tours, page component describers and other sequential information displays with Bootstrap popovers in a quick and easy way, using Bootstrap Tour.

### **Parameters**

Quick and easy way to build your product tours with Driver.js Introduced in Tiki 15. Required parameters are in **bold**. Go to the source code Preferences required: wikiplugin tour

**Parameters** Accepted Description Default Since Values (body of plugin) Content of the step title text Title of the step 15.0 element text Element to show the popup on; if empty, use the 15.0 plugin location itself text Text to show on the Next button. (Set only in the Next 27.0next\_button\_text first step.) int Number of steps in the tour. (Set only in the first 27.0 number\_of\_steps step.) overlay\_color text Set an overlay color to be shown behind the transparent 27.0 popover and its element, highlighting the current step. (Set only in the first step.) 27.0 overlay\_opacity int Set the opacity of the overlay. (Set only in the first 0.5 step.) prev\_button\_text text Text to show on the Prev button. (Set only in the Previous 27.0first step.) progress\_text Template for the progress text. You can use the of 27.0 text following placeholders in the template: // - : The current step number. // - : Total number of steps. Example: Step of . (Set only in the first step.)

show_restart_button	text	Display a button to restart the tour. Enter the text to appear on the button. (Set only in the first step.)		15.0
tour_id	text	Set a tour ID to be able to only show the tour once. (Set only in the first step.)	default	15.0
align	end start center	The alignment of the popup. (Set only in the first step.)	end	15.0
animate	y n	Animate the popup. (Set only in the first step.)	У	27.0
show_once	(blank) y n	Show automatically only once. tour_id should also be set if there are multiple tours. (Set only in the first step.)	n	15.0
show_progress	y n	Show the progress text in popover. (Set only in the first step.)	n	27.0
side	right top bottom left	The side of the popup. (Set only in the first step.)	right	15.0
start	y n	Start the tour on page load? If "No", then a start button can be made with "Restart Button", below. (Set only in the first step.)	у	15.0
allow_close	y n	Allow closing the popover by clicking on the backdrop. (Set only in the first step.)	у	16.0

## Examples

The first step:

{TOUR(title="Welcome to the tour" prev="-1" element="#PluginTour")}Here's the start of a tour.{TOUR}

A middle step:

TOUR(title="A typical middle step")This step is neither first nor last on the page, isn't anchored to an element, and isn't an orphan. It's nothing special. TOUR

A step that specifies a page element:

 $\label{eq:tour} \end{tabular} $$ TOUR(element="module_1 .panel-heading" title="This is a module heading.") } This is a module. \\ \end{tabular}$ 

A step that indicates that the following step is on another page:

{TOUR(path="PluginTour-page-2")}This plugin has a title and body content, but these won't be displayed - this step is simply a redirect to the target page.{TOUR}

The last step:

{TOUR(next="-1")}This is the last step of the tour.{TOUR}

#### **Usage notes**

- For each step of the tour, input the Tour plugin syntax as shown above.
- The first and last steps need a prev="-1" and next="-1" parameter, respectively. Without these, the tour won't display correctly.
- If the tour isn't configured to start on page load (if *start*="*n*" is set), a start button can be made with the "show restart\_button" parameter.
- Each step will pop over the page element where the plugin syntax is input in the wiki page, etc.
- The position of the popup relative to the element it pops up over can be set with the *placement* parameter.
- To create a step that is positioned other than where the plugin syntax is input, use the element parameter to specify an HTML id or other unique selector.
- Use the path parameter to indicate that the next step is on another page. Simply using a wiki page name is OK.
- A tour plugin step that uses the path parameter doesn't itself display (it is not visible); it simply acts as a redirect, so it shouldn't be used to contain information. Any guidance to the user that the tour is continuing on another page should be inserted in the *previous* plugin step (as of May 2017).
- At this time, the "prev" button on the first step of the tour's second page is ghosted and doesn't work to return to the first page.

## Adding a tour to a page that doesn't have wiki text content

Normally, as described above, the tour plugins are written into the wiki text of the page(s) on which the tour displays. However, it is possible to have a tour on an admin page or other such page that doesn't have wiki text.

This method uses a module for the tour plugin text that is assigned to, for example, the pagebottom module zone. Since all the steps of the tour are in the admin page content (and not in the module zone), the *element* parameter is used for each step that needs to be located in the page. But not all page elements in an admin page have unique DOM selectors, or ones that are easy to identify, so the ability to have a tour with complete tour-step placement may be limited for some pages.



