

Security Site Access tab

Overview

Use this tab to configure how Tiki handles the security relating to site access.

Related Topics
• [security admin](#)

To Access

From the [Security Admin](#) page, click the **Site Access** tab.

Option	Description	Default
Close site	Use this setting to "close" the Tiki site (such as for maintenance). Users attempting to access the site will see only a log-in form. Only users with specific permission will be allowed to log in. Use the Message to display to specify the message that visitors will see when attempting to access your site.	Disabled
Title		Coming soon
Message		Site is closed for maintena...
Close site when server load is above the threshold	Use this option to "close" the Tiki site when the server load exceeds a specific threshold. Only users with specific permission will be allowed to log in. Use "Maximum average server load threshold in the last minute" to define the maximum server load. Use the "Message to display" to specify the message that visitors will see when attempting to access the site.	Disabled
Maximum average server load threshold in the last minute		3
Site Busy Title		Server too busy
Site Busy Message		Server is currently too bus...
Enable intrusion detection system	An intrusion detection system (IDS) is a device or software application that monitors a network or systems for malicious activity or policy violations.	Disabled

Option	Description	Default
Custom rules file		temp/ids_custom_rules.json
Intrusion detection system mode	Define IDS operation mode, log only, or log and block with impact over a given threshold. ☰ Log only Log and block requests	Log only
Intrusion detection system threshold	Define IDS threshold, when configured in "Log and block requests" more.	0
Log to file		ids.log
Log to database		Disabled

Option	Description	Default
Close site	Use this setting to "close" the Tiki site (such as for maintenance). Users attempting to access the site will see only a log-in form. Only users with specific permission will be allowed to log in. Use the Message to display to specify the message that visitors will see when attempting to access your site.	Disabled
Title		Coming soon
Message		Site is closed for maintena...
Close site when server load is above the threshold	Use this option to "close" the Tiki site when the server load exceeds a specific threshold. Only users with specific permission will be allowed to log in. Use "Maximum average server load threshold in the last minute" to define the maximum server load. Use the "Message to display" to specify the message that visitors will see when attempting to access the site.	Disabled
Maximum average server load threshold in the last minute		3
Site Busy Title		Server too busy
Site Busy Message		Server is currently too bus...

Option	Description	Default
Enable intrusion detection system	An intrusion detection system (IDS) is a device or software application that monitors a network or systems for malicious activity or policy violations.	Disabled
Custom rules file		temp/ids_custom_rules.json
Intrusion detection system mode	Define IDS operation mode, log only, or log and block with impact over a given threshold. ☰ Log only Log and block requests	Log only
Intrusion detection system threshold	Define IDS threshold, when configured in "Log and block requests" more.	0
Log to file		ids.log
Log to database		Disabled

Option	Description	Default
Close site	Use this setting to "close" the Tiki site (such as for maintenance). Users attempting to access the site will see only a log-in form. Only users with specific permission will be allowed to log in. Use the Message to display to specify the message that visitors will see when attempting to access your site.	Disabled
Title		Coming soon
Message		Site is closed for maintena...
Close site when server load is above the threshold	Use this option to "close" the Tiki site when the server load exceeds a specific threshold. Only users with specific permission will be allowed to log in. Use "Maximum average server load threshold in the last minute" to define the maximum server load. Use the "Message to display" to specify the message that visitors will see when attempting to access the site.	Disabled
Maximum average server load threshold in the last minute		3

Option	Description	Default
Site Busy Title		Server too busy
Site Busy Message		Server is currently too bus...
Enable intrusion detection system	An intrusion detection system (IDS) is a device or software application that monitors a network or systems for malicious activity or policy violations.	Disabled
Custom rules file		temp/ids_custom_rules.json
Intrusion detection system mode	Define IDS operation mode, log only, or log and block with impact over a given threshold. ☰ Log only Log and block requests	Log only
Intrusion detection system threshold	Define IDS threshold, when configured in "Log and block requests" more.	0
Log to file		ids.log
Log to database		Disabled

Option	Description	Default
Close site	Use this setting to "\"close\" the Tiki site (such as for maintenance). Users attempting to access the site will see only a log-in form. Only users with specific permission will be allowed to log in. Use the Message to display to specify the message that visitors will see when attempting to access your site.	Disabled
Title		Coming soon
Message		Site is closed for maintena...
Close site when server load is above the threshold	Use this option to "close" the Tiki site when the server load exceeds a specific threshold. Only users with specific permission will be allowed to log in. Use "Maximum average server load threshold in the last minute" to define the maximum server load. Use the "Message to display" to specify the message that visitors will see when attempting to access the site.	Disabled

Option	Description	Default
Maximum average server load threshold in the last minute		3
Site Busy Title		Server too busy
Site Busy Message		Server is currently too bus...
Enable intrusion detection system	An intrusion detection system (IDS) is a device or software application that monitors a network or systems for malicious activity or policy violations.	Disabled
Custom rules file		temp/ids_custom_rules.json
Intrusion detection system mode	Define IDS operation mode, log only, or log and block with impact over a given threshold. ☰ Log only Log and block requests	Log only
Intrusion detection system threshold	Define IDS threshold, when configured in "Log and block requests" more.	0
Log to file		ids.log
Log to database		Disabled

Option	Description	Default
Close site	Use this setting to "\"close\" the Tiki site (such as for maintenance). Users attempting to access the site will see only a log-in form. Only users with specific permission will be allowed to log in. Use the Message to display to specify the message that visitors will see when attempting to access your site.	Disabled
Title		Coming soon
Message		Site is closed for maintena...

Option	Description	Default
Close site when server load is above the threshold	Use this option to "close" the Tiki site when the server load exceeds a specific threshold. Only users with specific permission will be allowed to log in. Use "Maximum average server load threshold in the last minute" to define the maximum server load. Use the "Message to display" to specify the message that visitors will see when attempting to access the site.	Disabled
Maximum average server load threshold in the last minute		3
Site Busy Title		Server too busy
Site Busy Message		Server is currently too bus...
Enable intrusion detection system	An intrusion detection system (IDS) is a device or software application that monitors a network or systems for malicious activity or policy violations.	Disabled
Custom rules file		temp/ids_custom_rules.json
Intrusion detection system mode	Define IDS operation mode, log only, or log and block with impact over a given threshold. ☰ Log only Log and block requests	Log only
Intrusion detection system threshold	Define IDS threshold, when configured in "Log and block requests" more.	0
Log to file		ids.log
Log to database		Disabled

Close site

Activated with the "Close site when server load is above the threshold" or "Close Site" preferences. The site will be closed but allow groups with *tiki_p_access_closed_site* permission to log in.

The page displayed when the site is closed is generated from a template HTML file called *templates/styles/site_closed.html*. If you want to customise this, it is recommended you make a copy of it called *site_closed_local.html* and edit that. This will be used in preference to the standard one if found.

The following "tags" will be replaced in the HTML:

{title}

Page title and H1 tags

{error}

Text displayed under the title heading

{login}

The login form

{back}

A browser back button (probably will be removed because this doesn't always make sense)

Alias: [Site Closed](#)

Alias: [Close Site](#)