Windows Server Install
Windows 2008R2 Server setup
[-] This documentation provides detailed notes on a successful new installation of Tiki4.0 on a Windows 2008R2 Server.
Hopefully this will allow more TikiWiki users to take advantage of a Windows/IIS environment without the need of a WAMP install.
URL Rewrite module
Proper operation of Tiki versions prior to 8 on IIS requires that the URL Rewrite module for IIS is installed. • Download the URL Rewrite Module.
Special setup for img tracker field type Special setup to show uploaded images from tracker field img is needed. please see here: Image Tracker Field

Software used:

- Windows2008R2 Server Standard Edition (x64) IIS 7
- MySQL 5.1.41 (x64) Community Edition
- MySQL GUI tools 5.0-r17-win32 (optional, but much easier)
- PhP 5.3.1 nts-Win32-VC9 (x86)

Installed Windows:

- Joined Domain, set static IP. (Running as Administrator)
- Added IIS Role
- Features for IIS:

Common HTTP Features

- Static Content
- Default Document
- Directory Browsing
- HTTP Errors
- HTTP Redirection

Application Development

- ASP.NET
- .Net Extensibility
- CGI
- ISAPI Extensions
- ISAPI Filters

Health and Diagnostics

- HTTP Logging
- Request Monitor

Security

• Request Filtering

Performance

• Static Content Compression

Management Tools

• IIS Management Console

_

Windows: Turned off IE Enhanced Security

Windows: Ran MS Update installed all important and all optional updates.

Windows: Reboot server

Installed other software

Installed MySQL (x64) all defaults.

Installed MySQL GUI Tools.

Installed PHP 5.3.1 (x86) default settings installed to C:\PHP

Windows: Created C:\Temp directory

Windows: Under Security Settings, added everyone with full permissions to the following

direc__tories:
 *C:\inetpub\wwwroot\

- C:\PHP\
- C:\Program files\MySQL
- C:\Temp

Edited PHP.INI

- include_path = ".;c:\php\includes" uncommented (line 787)
- cgi.force_redirect = 1 uncommented (line 822)
- fastcgi.impersonate = 1; uncommented (line 850)
- upload_tmp_dir="C:\temp" changed from c:\windows\temp (line 908)
- session.save path="C:\temp" changed from c:\windows\temp (line 909)
- error_log="C:\temp\php-errors.log" changed from c:\windows\temp (line 910)
- date.timezone = America/New York changed from blank (line 962)
- sendmail_from = my email address changed from blank (line 1056)

Windows: Opened port 3306 in windows firewall for remote MySQL client tools access.

Windows: Unzipped TikiWiki 4.0 to c:\inetpub\wwwroot\tw4

Windows: Created a phpinfo.php file in c:\inetpub\wwwroot to validate the php install.

From LAN workstation:

Verified MySQL remote connectivity and using MySQL Query Browser, created a new schema (database) named Tiki4.

Opened IE8 and connected to the phpinfo.php page to verify PHP install and settings.

Take dog for walk and hoping for success!

From LAN workstation, opened FireFox Browser and pointed to the tw4 path, and got the tikiinstall.php page.

-	
TikiWiki 4.0 Install	
[+]	
Select your language: English	
Click continue	
read the license	
click continue	

Review the System Requirements
Memory: Tiki has detected your PHP memory_limit at: 128 MB. mail: did not test (have not set mail server yet) Image Processing: Tiki detected: GD bundled (2.0.34 compatible). click continue
Set the Database Connection
Database Type, MySOL Improved (mysali) Requires MySOL 4.1.
Database Type: MySQL Improved (mysqli). Requires MySQL 4.1+
Host name: 192.168.0.40 Database name: tw4
• Host name: 192.168.0.40
 Host name: 192.168.0.40 Database name: tw4 Database User: root

Install - A new install will populate the database.

click install

Review the Installation
Installation complete
Installation operations executed successfully: 5469 SQL queries. click continue
Configure General Settings
Browser Title: KCDI Intranet
Sender email: my email address HTTPS login: Disabled (no change)
Admin email: my email address click to continue
Click to continue
Enter Your Tiki
click Enter Tiki and Lock Installer (Recommended)

HomePage

Congratulations

This is the default HomePage for your Tiki. If you are seeing this page, your installation was successful.

admin / admin click login

Change password enforced

old password: admin new password: ******* repeat password: *******

click change

HomePage

Edit Section

Edit Section

Thank you for installing Tiki.

The entire Tiki Community would like to thank you and help you get introduced to Tiki.

Aliases

Windows Server | Windows Server

[-] (Spring 2010 notes by jonnyb)	

Issues (install from svn HEAD)

Notes from IIS project for Tiki 5

- Writable dirs not detected (by installer or tiki main)
 - Caused major issues, but only had to set /temp, /templates_c and db/local.php to run
- Mail errors from zend on smtp (default installation)
 - SMTP probably not running on server
 - Then needs tying into PHP?
 - Tiki SMTP is broken (fails with a timeout, on Windows as well as Unix). Chealer9 20100709
- file write error on new tpls

example error

PHP (5.2.12) ERROR (E_WARNING): File:

C:\inetpub\wwwroot\tiki\lib\smarty\libs\internals\core.write_file.php Line: 44 Type: unlink(C:\inetpub\wwwroot\tiki\templates_c\ en^%%23^230^230491F8%%tiki-list_blogs.tpl.php) [function.unlink]: No such file or directory

 That function blindly asks to delete a file without knowing whether it exists. This should be fine and most performant (since it saves a filesystem operation) using the PHP @ error-quieting operator, but that operator has no effect on Tiki since it uses custom error handling. This could be considered a PHP/Smarty bug highlighted by Tiki. We have a similar problem with php-openid. Chealer9 20100709

-

TikiWiki 5.0 Beta1 Install

I created a new Windows 2008R2 virtual server and using the basics listed above, installed 5.0 Beta 1 successfully.

I decided to use the latest software available, and ran into database errors during the Tiki installation with PHP 5.3.2 nts-Win32-VC9 (x386). This could have resulted in missing a line in the php.ini file, but I am pretty certain everything was in order. After starting over, I went back to 5.3.1 and had no issues.

I also used the latest version of MySQL (5.1.45 x64) with no problems.

https://wikisuite.org/How-to-install-WikiSuite-on-Windows-Server

Everything else was standard as per above.

Once I had a successful database creation, the page that came up looked like plain html. No formatting at all. However, I was able to change admin password and get into the site. After checking on #tikiwiki, Caarrie pointed me to Admin/Performance. There I unchecked the \tilde{A} ¢ \hat{a} , $\neg \hat{A}$ "Minify CSS \tilde{A} ¢ \hat{a} , $\neg \hat{A}$ and all of the formatting was perfect! (Thanks again Caarrie). I am not sure if this is a default setting on installation, but if you run into this problem, it is a simple fix.

Related links